



Olympus Table Specifications:

Olympus features heavy duty 14 gauge dual column T-Legs with welded mounting plates and welded steel endcaps. Tables 60" and longer include steel support to prevent sagging. Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Standard edges are T-mold and 3mm PVC. Other edges available*

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

*Custom edges may not be available with all shapes and sizes.

Web link: http://www.specialt.net/tables/training_room_tables/174

Base Construction:

- Welded/Bolted
- Table height: 29"
- Columns: 2" diameter, 14 gauge steel
- Feet: 2" diameter, 14 gauge steel, steel endcaps
- Mounting plates: 5" x 11", 6" x 16" or (2) 6" x 6"
- Levelers: 1-3/8" diameter, 1" long
- Finish: powder coat
- Load capacity: 330 lbs. (200kg) vertical load rating per base



Options:

- Grommets
- Wire management
- Power management

Additional Information:

- For easy installation, tops are pre-drilled.
- **Olympus** is available in multiple shapes, 36" - 60" width and up to 120" long. Tables over 96" long include a third leg.
- Standard lead time is 15 business days. Large orders may require additional time.



Compliant with
BIFMA X7.1 Standard