

# SPECIAL T

## **Benton Table Specifications:**

### **Top Construction:**

**Benton** features heavy duty 14 gauge H-Legs with all-welded construction. Tables 60" and longer include steel support to prevent sagging. Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Standard edges are T-mold and 3mm PVC. Other edges available\*

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

*\*Custom edges may not be available with all shapes and sizes.*

*Web link: [http://www.specialt.net/tables/training\\_room\\_tables/178](http://www.specialt.net/tables/training_room_tables/178)*

### **Base Construction:**

- Welded
- Table height: 29"
- Columns: 3" diameter, 14 gauge steel
- Mounting Plates: (2) 6" x 6" x 7/32" steel
- Levelers: 1-3/8" diameter allow additional 1" upward height adjustment
- Finish: powder coat
- Load capacity: 330 lbs. (200kg) vertical load rating per base

### **Options:**

- Grommets
- Wire management
- Power and data management

### **Additional Information:**

- For easy installation, tops are pre-drilled.
- Benton is available in various shapes, 36"- 48" width and up to 120" long. Tables over 96" long include a third leg.
- Standard lead time is 15 business days. Large orders may require additional time.



Compliant with  
BIFMA X7.1 Standard