

# SPECIAL T

## **Bedford Table Specifications:**

**Bedford** features X-base with four columns. Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Standard edges are T-mold and 3mm PVC. Other edges available\*

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurWood Urethane

*\*Custom edges may not be available with all shapes and sizes.*

*Web link: [http://www.specialt.net/tables/training\\_room\\_tables/156](http://www.specialt.net/tables/training_room_tables/156)*

### **Base Construction:**

- Rigid bolted
- Table height: 29"
- Columns: 2" diameter, 14 gauge steel
- Feet: 2" diameter, 14 gauge steel; steel endcaps
- Mounting plates: (4) " x 4" x 7/32" steel
- Levelers: 1-3/8" diameter, 1" long stud
- Finish: powder coat or optional polished chrome

### **Options:**

- Locking casters
- Polished chrome
- Bar height
- Self leveling glides
- Grommet
- Power management

### **Additional Information:**

- **Bedford** is available in round and square shapes.
- Round tables are not available with 3mm PVC edge.
- Standard lead time is 15 business days. Large orders may require additional time.



Compliant with  
BIFMA X7.1 Standard