



## **Astra Table Specifications:**

### **Top Construction:**

Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Standard edges are T-mold and 3mm PVC. Other edges available\*:

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

*\*Custom edges may not be available with all shapes and sizes.  
See [www.SpecialT.net](http://www.SpecialT.net) → product page → edge tab for edge offerings.*

### **Base Construction:**

Rigid bolted  
Table height: 29"  
3 columns: 3" diameter  
Round floor plate: cover plate is 1mm thick 304 grade sunray brushed stainless steel  
3 mounting plate: 13-3/4" x 13-3/4" x 1/8" pressed milled steel  
Levelers: 3/4" diameter  
Finish: stainless steel  
Load capacity: 500 lbs. vertical load rating per base

### **Options:**

- Grommet
- Power management

### **Additional Information**

- **Astra** is available in round shape, 54" - 60" diameter.
- Standard lead time is 15 business days. Large orders may require additional time.



Compliant with  
BIFMA X7.1 Standard